Revised On 01/03/2020

15-25%

≥20-≤25%

15-25%

10-15%

5-10%

5-10%

1 Identification of the substance and manufacturer

1 Identification of the substance and manufacturer		
Trade name:	UNIVERSAL GOLD	
Product code: Recommended use: Uses advised against: Manufacturer/Supplier: Emergency telephone number:	EN00500000 Paint and coatings application. Any that differs from the recommended use. Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com 1-800-255-3924	Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com
2 Hazard(s) identification		
Classification of the substance or	mixture	
Flam. Aerosol 1 H222 Extremely fla		
	s under pressure; may explode if heated.	
Skin Irrit. 2 H315 Causes skin		
Eye Irrit. 2A H319 Causes serie		
5	e fertility or the unborn child.	
	drowsiness or dizziness.	
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.		
GHS Hazard pictograms	GHS02 GHS04 GHS07 GHS08	
Signal word Hazard statements	Danger Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May damage fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or re	epeated exposure.
Precautionary statements	Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even aft Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protect IF INHALED: Remove person to fresh air and keep co If in eyes: Rinse cautiously with water for several mi easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label)	tion/face protection. brofortable for breathing.

Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place.

Store locked up. Protect from sunlight

86376-49-0 Brass Powder (Alloy)

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients Chemical characterization: Mixtures Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions. Dangerous components: 67-64-1 Acetone 108-88-3 Toluene 74-98-6 propane 106-97-8 n-butane 110-19-0 Isobutyl Acetate

4 First-aid measures	
After inhalation: After skin contact:	Supply fresh air; consult doctor in case of complaints. Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. (Contd. on page 2)

Safety Data Sheet

Printing date 01/10/2020

Revised On 01/03/2020

	(Contd. of pag
After swallowing:	Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects:	Dizziness
Indication of any immediate medic	
attention needed:	No further relevant information available.
Fire-fighting measures	
Extinguishing agents: Special hazards:	CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.
Protective equipment for firefighters:	A respiratory protective device may be necessary.
menginers.	
Accidental release measures	
Personal precautions, protective equipment and emergency	
procedures:	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up:	Ensure adequate ventilation.
containing api	Dispose contaminated material as waste according to section 13.
' Handling and storage	
Precautions for safe handling	Use only in well ventilated areas.
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up.
Exposure controls/personal pro	otection
• • •	require monitoring at the workplace:
67-64-1 Acetone	
PEL (USA) Long-term value: 2400 m	ng/m³, 1000 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg	ng/m³, 1000 ppm g/m³, 250 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m	ng/m³, 1000 ppm g/m³, 250 ppm ng/m³, 500 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg	ng/m³, 1000 ppm g/m³, 250 ppm ng/m³, 500 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene	ng/m³, 1000 ppm g/m³, 250 ppm ng/m³, 500 ppm g/m³, 250 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) Long-term value: 200 pp	ng/m³, 1000 ppm g/m³, 250 ppm ng/m³, 500 ppm g/m³, 250 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene	mg/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 500 ppm g/m ³ , 250 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m	ng/m ³ , 1000 ppm g/m ³ , 250 ppm g/m ³ , 500 ppm g/m ³ , 250 ppm ^m 500* ppm hift g/m ³ , 150 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene E PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m Long-term value: 375 mg Stort-term value: 375 mg	ng/m ³ , 1000 ppm g/m ³ , 250 ppm g/m ³ , 500 ppm g/m ³ , 250 ppm ^m 500* ppm hift g/m ³ , 150 ppm g/m ³ , 150 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m	ng/m ³ , 1000 ppm g/m ³ , 250 ppm g/m ³ , 500 ppm g/m ³ , 250 ppm ^m 500* ppm hift g/m ³ , 150 ppm g/m ³ , 150 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene Ceiling limit value: 200 pp PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m Long-term value: 375 mg Long-term value: 75 mg/ TLV (USA) Long-term value: 75 mg/ BEI Ceiling limit value: 75 mg/	ng/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 500 ppm g/m ³ , 250 ppm ^m 500* ppm hift g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 20 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene Ceiling limit value: 200 pp PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m Long-term value: 375 mg Long-term value: 75 mg/ TLV (USA) Long-term value: 75 mg/ BEI PEL (USA) PEL (USA) Long-term value: 75 mg/ BEI PEL (USA) Degeter value: 1800 m	ng/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 500 ppm g/m ³ , 250 ppm hift g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 100 ppm /m ³ , 20 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 1187 m Long-term value: 594 mg BEI BEI 108-88-3 Toluene Ceiling limit value: 200 pp PEL (USA) Long-term value: 200; 4 *10-min peak per 8-hr sh Short-term value: 300; 4 REL (USA) Short-term value: 560 m Long-term value: 375 mg Long-term value: 75 mg TLV (USA) Long-term value: 75 mg BEI Degle 74-98-6 propane PEL (USA) PEL (USA) Long-term value: 1800 m REL (USA) Long-term value: 1800 m	ng/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 250 ppm g/m ³ , 250 ppm nift g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 100 ppm mg/m ³ , 1000 ppm ng/m ³ , 1000 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 1187 m Long-term value: 594 mg BEI BEI 108-88-3 Toluene Ceiling limit value: 200 pp PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m Long-term value: 375 mg BEI TLV (USA) Long-term value: 75 mg/ BEI Deg-term value: 1800 m REL (USA) Long-term value: 1800 m	ng/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 250 ppm g/m ³ , 250 ppm nift g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 100 ppm mg/m ³ , 1000 ppm ng/m ³ , 1000 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m Long-term value: 375 mg BEI TLV (USA) Long-term value: 75 mg/ BEI Long-term value: 1800 m REL (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1800 m REL (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1800 m REL (USA) Long-term value: 1800 m TLV (USA) refer to Appendix F inTLY 106-97-8 n-butane Tube	ng/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 250 ppm g/m ³ , 250 ppm hift g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 100 ppm mg/m ³ , 1000 ppm ng/m ³ , 1000 ppm Ng/m ³ , 1000 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 360 m Long-term value: 375 mg BEI TLV (USA) Long-term value: 75 mg/ BEI Long-term value: 75 mg BEI Long-term value: 1800 m TLV (USA) Long-term value: 1800 m REL (USA) Long-term value: 1800 m TLV (USA) Long-term value: 2370 m TLV (USA) Long-term value: 1900 m TLV (USA) Short-term value: 2370 m	ng/m ³ , 1000 ppm g/m ³ , 250 ppm g/m ³ , 250 ppm g/m ³ , 250 ppm j/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 100 ppm fm ³ , 20 ppm ng/m ³ , 1000 ppm vs&BEls book; D, EX
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m Long-term value: 375 mg BEI TLV (USA) Long-term value: 75 mg/ BEI USA) Long-term value: 75 mg/ BEI Dog-term value: 1800 m TLV (USA) Long-term value: 1800 m REL (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1900 m TLV (USA) Short-term value: 2370 m KEL (USA) Long-term value: 2370 m KEL (USA) Short-term value: 2370 m	ng/m ³ , 1000 ppm g/m ³ , 250 ppm g/m ³ , 250 ppm g/m ³ , 250 ppm j/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 100 ppm fm ³ , 20 ppm ng/m ³ , 1000 ppm vs&BEls book; D, EX
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m Long-term value: 375 mg BEI TLV (USA) Long-term value: 75 mg/ BEI USA) Long-term value: 75 mg/ BEI Cong-term value: 1800 m TLV (USA) Long-term value: 1800 m REL (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1900 m TLV (USA) Short-term value: 2370 m (EX) 110-19-0 Isobutyl Acetate	ng/m³, 1000 ppm g/m³, 250 ppm ng/m³, 500 ppm g/m³, 250 ppm m 500* ppm j/m³, 150 ppm g/m³, 150 ppm g/m³, 100 ppm mg/m³, 1000 ppm ng/m³, 1000 ppm vs&BEIs book; D, EX
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 1187 m Long-term value: 594 mg BEI BEI 108-88-3 Toluene Ceiling limit value: 300; 4 PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m Long-term value: 375 mg BEI 74-98-6 propane DEL (USA) PEL (USA) Long-term value: 1800 m REL (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1900 m TLV (USA) Short-term value: 2370 m (EX) Short-term value: 2370 m	ng/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 250 ppm 500* ppm iift g/m ³ , 150 ppm g/m ³ , 100 ppm mg/m ³ , 1000 ppm ng/m ³ , 1000 ppm vs&BEIs book; D, EX
PEL (USA)Long-term value: 2400 mREL (USA)Long-term value: 590 mgTLV (USA)Short-term value: 1187 mLong-term value: 1187 mLong-term value: 594 mgBEI108-88-3 ToluenePEL (USA)Long-term value: 200 ppCeiling limit value: 300; 4*10-min peak per 8-hr shREL (USA)Short-term value: 360 mLong-term value: 375 mgTLV (USA)Long-term value: 75 mg/BEI74-98-6 propanePEL (USA)Long-term value: 1800 mREL (USA)Long-term value: 1800 mTLV (USA)Long-term value: 1800 mTLV (USA)Long-term value: 2370 mTLV (USA)Short-term value: 2370 m(EX)110-19-0 Isobutyl AcetatePEL (USA)Long-term value: 700 mgREL (USA)Long-term value: 700 mgTLV (USA)Short-term value: 700 mgTLV (USA)Short-term value: 700 mgREL (USA)Long-term value: 700 mgTLV (USA)Short-term value: 712 m	ng/m³, 1000 ppm g/m³, 250 ppm ng/m³, 250 ppm g/m³, 250 ppm m 500° ppm hift g/m³, 150 ppm g/m³, 100 ppm ng/m³, 1000 ppm vs&BEIs book; D, EX ng/m³, 100 ppm ng/m³, 100 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m Long-term value: 375 mg Long-term value: 75 mg/ TLV (USA) Long-term value: 75 mg/ BEI 106-97-8 n-butane REL (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1800 m TLV (USA) Long-term value: 2370 m REL (USA) Long-term value: 2370 m TLV (USA) Short-term value: 2370 m TLV (USA) Long-term value: 700 mg REL (USA) Long-term value: 712 m <td< td=""><td>ng/m³, 1000 ppm g/m³, 250 ppm ng/m³, 500 ppm g/m³, 250 ppm 500* ppm iift g/m³, 150 ppm g/m³, 1000 ppm ng/m³, 1000 ppm Vs&BEIs book; D, EX ng/m³, 1000 ppm g/m³, 150 ppm g/m³, 150 ppm g/m³, 150 ppm g/m³, 150 ppm</td></td<>	ng/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 500 ppm g/m ³ , 250 ppm 500* ppm iift g/m ³ , 150 ppm g/m ³ , 1000 ppm ng/m ³ , 1000 ppm Vs&BEIs book; D, EX ng/m ³ , 1000 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m Long-term value: 375 mg Long-term value: 75 mg/ TLV (USA) Long-term value: 75 mg/ BEI Long-term value: 1800 m TLV (USA) Long-term value: 2370 m TLV (USA) Long-term value: 2370 m TLV (USA) Long-term value: 200 m TLV (USA) Long-term value: 700 m REL (USA) Long-term value: 700 m	ng/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 500 ppm g/m ³ , 250 ppm 500* ppm iift g/m ³ , 150 ppm g/m ³ , 1000 ppm ng/m ³ , 1000 ppm Vs&BEIs book; D, EX ng/m ³ , 1000 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m Long-term value: 375 mg Long-term value: 75 mg/ TLV (USA) Long-term value: 75 mg/ BEI Long-term value: 1800 m TLV (USA) Long-term value: 200 m TLV (USA) Long-term value: 700 mg REL (USA) Long-term value: 700 mg <t< td=""><td>ng/m³, 1000 ppm g/m³, 250 ppm ng/m³, 500 ppm g/m³, 250 ppm 500* ppm iift g/m³, 150 ppm g/m³, 1000 ppm ng/m³, 1000 ppm Vs&BEIs book; D, EX ng/m³, 1000 ppm g/m³, 150 ppm g/m³, 150 ppm g/m³, 150 ppm g/m³, 150 ppm</td></t<>	ng/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 500 ppm g/m ³ , 250 ppm 500* ppm iift g/m ³ , 150 ppm g/m ³ , 1000 ppm ng/m ³ , 1000 ppm Vs&BEIs book; D, EX ng/m ³ , 1000 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 360 m Long-term value: 375 mg BEI 74-98-6 propane E PEL (USA) Long-term value: 75 mg/ BEI Long-term value: 1800 m TLV (USA) Long-term value: 1900 m TLV (USA) Short-term value: 2370 m TLV (USA) Long-term value: 200 mg REL (USA) Long-term value: 200 mg REL (USA) Long-term value: 200 mg REL (USA) Long-term value: 700 mg REL (USA) Short-term value: 712 m Long-term value: 238 mg <td< td=""><td>ng/m³, 1000 ppm g/m³, 250 ppm ng/m³, 500 ppm g/m³, 250 ppm 500* ppm iift g/m³, 150 ppm g/m³, 1000 ppm ng/m³, 1000 ppm Vs&BEIs book; D, EX ng/m³, 1000 ppm g/m³, 150 ppm g/m³, 150 ppm g/m³, 150 ppm g/m³, 150 ppm</td></td<>	ng/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 500 ppm g/m ³ , 250 ppm 500* ppm iift g/m ³ , 150 ppm g/m ³ , 1000 ppm ng/m ³ , 1000 ppm Vs&BEIs book; D, EX ng/m ³ , 1000 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 150 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 560 m Long-term value: 375 mg TLV (USA) Short-term value: 75 mg/ BEI 74-98-6 propane E PEL (USA) Long-term value: 1800 m REL (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1800 m REL (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1900 m TLV (USA) Short-term value: 2370 m (EX) Long-term value: 2370 m TLV (USA) Long-term value: 700 mg REL (USA) Long-term value: 700 mg REL (USA) Long-term value: 712 m Long-term value: 238 mg Ingredients with biological limit value 67-64-1 Ace	ng/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 250 ppm ^m 500* ppm ift g/m ³ , 150 ppm g/m ³ , 100 ppm ng/m ³ , 1000 ppm ng/m ³ , 1000 ppm vs&BEIs book; D, EX ng/m ³ , 1000 ppm g/m ³ , 150 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 360 m Long-term value: 375 mg BEI 74-98-6 propane Deg term value: 1800 m PEL (USA) Long-term value: 1800 m REL (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1900 m TLV (USA) Short-term value: 2370 m REL (USA) Long-term value: 2370 m TLV (USA) Short-term value: 700 mg REL (USA) Long-term value: 700 mg REL (USA) Long-term value: 712 m Long-term value: 238 mg Ingredients with biological limit value	ng/m ³ , 1000 ppm g/m ³ , 250 ppm g/m ³ , 250 ppm g/m ³ , 250 ppm ift g/m ³ , 150 ppm g/m ³ , 150 ppm g/m ³ , 1000 ppm ng/m ³ , 1000 ppm vs&BEIs book; D, EX ng/m ³ , 1000 ppm g/m ³ , 150 ppm
PEL (USA) Long-term value: 2400 m REL (USA) Long-term value: 590 mg TLV (USA) Short-term value: 1187 m Long-term value: 1187 m Long-term value: 594 mg BEI 108-88-3 Toluene PEL (USA) Long-term value: 200 pp Ceiling limit value: 300; 4 *10-min peak per 8-hr sh REL (USA) Short-term value: 360 m Long-term value: 375 mg BEI 74-98-6 propane Long-term value: 1800 m PEL (USA) Long-term value: 1800 m REL (USA) Long-term value: 1800 m TLV (USA) Long-term value: 1900 m TLV (USA) Short-term value: 2370 m REL (USA) Long-term value: 2370 m REL (USA) Long-term value: 700 mg REL (USA) Long-term value: 700 mg REL (USA) Long-term value: 712 m Long-term value: 238 mg Ingredients with biological limit value	ng/m ³ , 1000 ppm g/m ³ , 250 ppm ng/m ³ , 250 ppm ^m 500* ppm ift g/m ³ , 150 ppm g/m ³ , 100 ppm ng/m ³ , 1000 ppm ng/m ³ , 1000 ppm vs&BEIs book; D, EX ng/m ³ , 1000 ppm g/m ³ , 150 ppm

Page 3/4

Trade name: UNIVERSAL GOLD	
	(Contd. of page 2)
	Store protective clothing separately.
	Avoid contact with the eyes and skin. Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Hand protection:	Nitrile gloves.
·	The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles

9 Physical and chemical properties

3	i nysicai anu chennicai properties	
	Appearance: Odor: Odor threshold:	Aerosol. Aromatic Not determined.
	pH-value: Melting point/Melting range Boiling point:	Not determined. Undetermined. -44 °C (-111.2 °F)
	Flash point: Flammability (solid, gas):	-19 °C (-66.2 °F) Extremely flammable.
	Decomposition temperature:	Not determined.
	Auto igniting:	Product is not self-igniting.
	Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. 1.5 Vol % 10.9 Vol %
	Vapor pressure: Relative Density: Vapor density Evaporation rate Partition coefficient: n-octonal/water:	Not determined. Between 0.77 and 0.85 (Water equals 1.00) Not determined. Not applicable. Not determined.
	Solubility: Viscosity: VOC content (less exempt solvents):	Not determined. Not determined. 38.5 %

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing
	temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:	
106-97-8 n-butane	
Inhalative LC50/4 h 658 mg/l (rat)	
110-19-0 Isobutyl Acetate	
Oral LD50 4,763 mg/kg (rbt)	
Information on toxicological effects: No data available.	
Skin effects: Irritant to skin and mucous membranes.	
Eye effects: Irritating effect.	
Sénsitization: No sensitizing effects known.	

12 Ecological information	
Aquatic toxicity: Persistence and degradability: Other information:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Bioaccumulative potential: Mobility in soil: Ecotoxical effects:	No further relevant information available. No further relevant information available.
Remark:	Toxic for fish (Contd. on page 4)

Revised On 01/03/2020

Page 4/4

Printing date 01/10/2020 Revised On 01/03/2020	
Trade name: UNIVERSAL GOLD	
Other adverse effects:	(Contd. of page 3) (Contd. of page 3)
13 Disposal considerations Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. Recommendation: Completely empty cans should be recycled.	
14 Transport information	
UN-Number DOT DOT ADR Transport hazard class(es): Class Marine pollutant: Special precautions for user: EMS Number: Segregation groups Packaging Group: UN "Model Regulation":	UN1950 N/A Consumer Commodity ORM-D Aerosols, flammable 1950 Aerosols 2.1 Yes Symbol (fish and tree) Warning: Gases F-D,S-U Heavy metals and their salts (including their organometallic compounds) UN1950, Aerosols, 2.1
15 Regulatory information	
SARA Section 355 (extremely hazar None of the ingredients in this product	
SARA Section 313 (Specific toxic cl	
108-88-3 Toluene	
Toxic Substances Control Act (TSCA): Canadian Domestic Substances Lis (DSL): Consumer Product Safety Comission (CPSC):	All hazardous ingredients are found on the inventory list of substances. All ingredients are listed or exempted. This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
California Proposition 65 chemicals	
None of the ingredients in this product	are listed.
Prop 65 chemicals known to cause 108-88-3 Toluene	birth defects or reproductive harm:
EPA: 67-64-1 Acetone 110-19-0 Isobutyl Acetate	 D
16 Other information	
Contact:	Regulatory Affairs