



BLACK WRINKLE PAINT #16-2448

Seymour's black wrinkle paint can reproduce the original factory finish on a variety of car and truck parts. This durable black coating resists gasoline, automotive fluids, fading, rust, corrosion, and chipping. It has excellent hiding qualities and can be used where conventional coatings break down.

Suggested Uses:

Metal dashboards
Ignition wire holders
Valve covers
Gun stocks
Beautify motorcycle engines
Tool handles for better grip

Packaging:

UPC Code	043281001281
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 7 square feet
Cleanup	Lacquer or paint thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	26%
MIR value	0.92, cannot exceed 0.95
Storage Temperature	40-90F
Application Temperature	50-100F
Abrasion Resistance	Very Good
Heat Resistance	250F
Gasoline Resistance	Yes
Resin System	Linseed and Tung Oil
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time:

To touch 30 minutes
8 hours is required to complete the wrinkling process

Gloss: Varies with pattern

Additional Information:

Two medium coats are needed to achieve the wrinkled texture, with the second coat applied approximately three minutes after the first. The wrinkling effect does not appear right away. Allow eight hours to cure.

12-20-2019