

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 1 of 13

## Top Coat Silver - Aerosol

### SECTION 1: Identification

#### Product identifier

**Product name:** Top Coat Silver - Aerosol

**Product code:** 46018



#### Recommended use of the product and restriction on use

**Relevant identified uses:** Used as a top coat for metal

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

#### Manufacturer or supplier details

##### Manufacturer:

##### United States

P.O.R. Products

38 Portman Road

New Rochelle, NY 10801

914-636-0700

#### Emergency telephone number:

##### United States

##### ChemTel Inc.

+1 800 255 3924

+1 813 248 0585

### SECTION 2: Hazard(s) identification

#### GHS classification:

Flammable aerosols, category 1

Compressed gases

Skin irritation, category 2

Eye irritation, category 2A


Skin sensitization, category 1

Carcinogenicity, category 2

Specific target organ toxicity - single exposure, category 3, central nervous system

#### Label elements

##### Hazard pictograms:



**Signal word:** Danger

#### Hazard statements:

H222 Extremely flammable aerosol

H280 Contains gas under pressure; may explode if heated

H229 Pressurized container: may burst if heated.

H315 Causes skin irritation

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

H351 Suspected of causing cancer

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 2 of 13

## Top Coat Silver - Aerosol

H336 May cause drowsiness or dizziness  
H315+H320 Causes skin and eye irritation.

### Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking  
P211 Do not spray on an open flame or other ignition source  
P251 Pressurized container. Do not pierce or burn, even after use  
P264 Wash skin thoroughly after handling  
P280 Wear protective gloves/protective clothing/eye protection/face protection  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray  
P272 Contaminated work clothing should not be allowed out of the workplace  
P201 Obtain special instructions before use  
P202 Do not handle until all safety precautions have been read and understood  
P271 Use only outdoors or in a well-ventilated area  
P281 Use personal protective equipment as required.  
P321 Specific treatment (see supplemental first aid instructions on this label).  
P362 Take off contaminated clothing and wash before reuse  
P302+P352 If on skin: Wash with soap and water  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing  
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention  
P308+P313 If exposed or concerned: Get medical advice/attention  
P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell  
P332+P313 If skin irritation occurs: Get medical advice/attention  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P337+P313 If eye irritation persists get medical advice/attention  
P363 Wash contaminated clothing before reuse  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
P410+P403 Protect from sunlight. Store in a well ventilated place  
P405 Store locked up  
P403+P233 Store in a well ventilated place. Keep container tightly closed  
P501 Dispose of contents and container as instructed in Section 13

**Hazards not otherwise classified:** None

## SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 64742-48-9	Hydrotreated Heavy Petroleum Naphtha	5-10
CAS number: 1330-20-7	Xylene	1-5
CAS number: 100-41-4	Ethyl Benzene	0.1-1
CAS number: 67-64-1	Acetone	10-30
CAS number: 74-98-6	Propane	10-30

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 3 of 13

## Top Coat Silver - Aerosol

CAS number: 64742-89-8	Vm&P Naphtha	10-30
CAS number: 540-88-5	T-Butyl Acetate	10-30

**Additional Information:** None

## SECTION 4: First aid measures

### Description of first aid measures

#### General notes:

Not determined or not applicable.

#### After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

#### After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

#### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Get medical advice if eye irritation persists

#### After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Not determined or not applicable.

#### Delayed symptoms and effects:

Not determined or not applicable.

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

Not determined or not applicable.

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media:

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 4 of 13

## Top Coat Silver - Aerosol

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

### Unsuitable extinguishing media:

Not determined or not applicable.

### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Contents under pressure

In a fire or if heated, a pressure increase will occur and the container may burst or explode

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere

### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

### Special precautions:

Shut off sources of ignition

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Beware of vapors accumulating to form explosive concentrations

Vapors can accumulate in low areas

### Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

### Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Use spark-proof tools and equipment

Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)

Dispose of contents / container in accordance with local regulations

### Reference to other sections:

Not determined or not applicable.

## SECTION 7: Handling and storage

### Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Do not puncture, crush, or incinerate containers, even when empty.

Protect cylinders from physical damage.

### Conditions for safe storage, including any incompatibilities:

Protect from freezing and physical damage.

Protect from direct sunlight.

Store in a cool, well-ventilated area.

Store cylinders upright.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 5 of 13

### Top Coat Silver - Aerosol

### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

#### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Propane	74-98-6	ACGIH TLV TWA 2,500 ppm
	Xylene	1330-20-7	ACGIH TWA: 100.0 ppm
	Xylene	1330-20-7	ACGIH STEL: 150.0 ppm
	T-Butyl Acetate	540-88-5	TLV TWA 8-hr: 50 ppm; STEL 15-min: 150 ppm
	Acetone	67-64-1	8-hour Exposure Limit (TLV-TWA): 250 ppm
	Acetone	67-64-1	15-minute STEL: 500 ppm
	Ethyl Benzene	100-41-4	ACGIH TWA: 20.0 ppm
	Ethyl Benzene	100-41-4	ACGIH STEL: 125.0 ppm
United States (OSHA)	Propane	74-98-6	OSHA PEL TWA 1,000 ppm (1,800 mg/m <sup>3</sup> )
	Xylene	1330-20-7	STEL: 655 mg/m <sup>3</sup> (150 ppm)
	Vm&P Naphtha	64742-89-8	PEL 100 ppm (400 mg/m <sup>3</sup> )
	T-Butyl Acetate	540-88-5	PEL: 950 mg/m <sup>3</sup> (200 ppm)
	Acetone	67-64-1	TWA: 750 ppm (1800 mg/m <sup>3</sup> )
	Acetone	67-64-1	STEL: 1000 ppm (2400 mg/m <sup>3</sup> )
	Hydrotreated Heavy Petroleum Naphtha	64742-48-9	OSHA Z-1 TWA 500 ppm (2,000 mg/m <sup>3</sup> )
	Xylene	1330-20-7	OSHA TWA: 435.0 mg/m <sup>3</sup> (100.0 ppm)
	Ethyl Benzene	100-41-4	OSHA PEL (STEL): 125.0 ppm
	Ethyl Benzene	100-41-4	OSHA TWA 100 ppm 435 mg/m <sup>3</sup>
	tert-Butyl acetate	540-88-5	TWA: 950 mg/m <sup>3</sup> (200 ppm)
	Acetone	67-64-1	TWA: 1185 mg/m <sup>3</sup> (500 ppm) ; STEL: 2375 mg/m <sup>3</sup> (1000 ppm)
	Xylene	1330-20-7	TWA: 350 mg/m <sup>3</sup> (80 ppm) ; STEL: 655 mg/m <sup>3</sup> (150 ppm)
NIOSH	Propane	74-98-6	NIOSH REL TWA 1,000 ppm (1,800 mg/m <sup>3</sup> )
	Vm&P Naphtha	64742-89-8	IDLH: 1000 ppm [Naphtha (Coal tar)]
	Vm&P Naphtha	64742-89-8	REL (for up to a 10-hour workday during a 40-hour workweek): 100 ppm (400 mg/m <sup>3</sup> ) [Naphtha (Coal tar)]
	T-Butyl Acetate	540-88-5	REL: 950 mg/m <sup>3</sup> (200 ppm)
	Acetone	67-64-1	REL (for up to a 10-hour workday during a 40-hour workweek): 250 ppm (590 mg/m <sup>3</sup> )
	Acetone	67-64-1	IDLH: 2500 ppm
	Xylene	1330-20-7	REL TWA: 435.0 mg/m <sup>3</sup> (100.0 ppm)

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 6 of 13

## Top Coat Silver - Aerosol

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Xylene	1330-20-7	REL ST: 655 mg/m <sup>3</sup> (150 ppm)
	Ethyl Benzene	100-41-4	NIOSH TWA 100.0 ppm 435.0 mg/m <sup>3</sup>
	Ethyl Benzene	100-41-4	NIOSH ST 125.0 ppm 545.0 mg/m <sup>3</sup>
Australia	T-Butyl Acetate	540-88-5	TWA: 950 mg/m <sup>3</sup> (200 ppm)
	Ethyl Benzene	100-41-4	TWA: 434 mg/m <sup>3</sup> (100 ppm); STEL: 543 mg/m <sup>3</sup> (125 ppm)
	Xylene	1330-20-7	TWA: 350 mg/m <sup>3</sup> (80 ppm) ; STEL: 655 mg/m <sup>3</sup> (150 ppm)
	Acetone	67-64-1	TWA: 1185 mg/m <sup>3</sup> (500 ppm) ; STEL: 2375 mg/m <sup>3</sup> (1000 ppm)
	Ethyl Benzene	100-41-4	TWA: 434 mg/m <sup>3</sup> (100 ppm); STEL: 543 mg/m <sup>3</sup> (125 ppm)

### Biological limit values:

No biological exposure limits noted for the ingredient(s).

### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above. Use explosion-proof ventilation equipment.

### Personal protection equipment

#### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

#### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

### General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Silver
Odor	Paint-like
Odor threshold	Not determined or not available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 7 of 13

## Top Coat Silver - Aerosol

<b>pH</b>	Not determined or not available.
<b>Melting point/freezing point</b>	> -95.30 °C
<b>Initial boiling point/range</b>	> 56.10 °C
<b>Flash point (closed cup)</b>	> -17.00 °C (Liquid); -104.40 °C (Propellant)
<b>Evaporation rate</b>	Not determined or not available.
<b>Flammability (solid, gas)</b>	Extremely Flammable Aerosol
<b>Upper flammability/explosive limit</b>	13.0%
<b>Lower flammability/explosive limit</b>	0.70%
<b>Vapor pressure</b>	Not determined or not available.
<b>Vapor density</b>	Not determined or not available.
<b>Density</b>	0.730 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined or not available.
<b>Solubilities</b>	Not determined or not available.
<b>Partition coefficient (n-octanol/water)</b>	Not determined or not available.
<b>Auto/Self-ignition temperature</b>	229.40 °C
<b>Decomposition temperature</b>	Not determined or not available.
<b>Dynamic viscosity</b>	Not determined or not available.
<b>Kinematic viscosity</b>	Not determined or not available.
<b>Explosive properties</b>	Not determined or not available.
<b>Oxidizing properties</b>	Not determined or not available.

### Other information

<b>Percent Volatile</b>	84.79 % wt
<b>Percent VOC</b>	45.86 % wt
<b>Percent HAP</b>	2.18 % wt
<b>Global Warming Potential</b>	0.93 GWP
<b>Ozone Depletion Potential</b>	0.00 ODP
<b>VOC Regulatory/Actual</b>	590.31 g/L (4.93 lbs/gal) / 334.75 g/L (2.79 lbs/gal)
<b>HAP Content</b>	15.91 g/L (0.13 lbs/gal)
<b>Maximum Incremental Reactivity</b>	0.7030 g O3/g

## SECTION 10: Stability and reactivity

### Reactivity:

Does not react under normal conditions of use and storage.

### Chemical stability:

Stable under normal conditions of use and storage.

### Possibility of hazardous reactions:

None under normal conditions of use and storage.

### Conditions to avoid:

Other Ignition Sources, Heat, Flames, Sparks.

### Incompatible materials:

Strong Oxidizing Agents, Strong Acids, Chlorosulfuric Acid.

### Hazardous decomposition products:

Acetic Acid.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 8 of 13

## Top Coat Silver - Aerosol

### SECTION 11: Toxicological information

#### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:**

Name	Route	Result
Xylene	dermal	LD50 - Rat - > 1,700 mg/kg
	inhalation	LC50 - Rat - 5,000 ppm/4 h
Ethyl Benzene	inhalation	LCLo - Rat - 4,000 ppm/4 h

#### Skin corrosion/irritation

**Assessment:** Causes skin irritation

**Product data:**

No data available.

**Substance data:**

Name	Result
Hydrotreated Heavy Petroleum Naphtha	Irritating to the skin.
Xylene	Irritating to the skin.

#### Serious eye damage/irritation

**Assessment:** Causes serious eye irritation

**Product data:**

No data available.

**Substance data:**

Name	Result
Acetone	Causes serious eye irritation.

#### Respiratory or skin sensitization

**Assessment:** May cause an allergic skin reaction

**Product data:**

No data available.

**Substance data:** No data available.

#### Carcinogenicity

**Assessment:** Suspected of causing cancer

**Product data:** No data available.

**Substance data:**

Name	Species	Result
Vm&P Naphtha	Solvent naphtha (petroleum), light aliphatic	The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

#### International Agency for Research on Cancer (IARC):

Name	Classification
Xylene	Group 3 - Not classifiable as to its carcinogenicity to humans
Ethyl Benzene	Group 2B - Possibly carcinogenic to humans



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 9 of 13

## Top Coat Silver - Aerosol

**National Toxicology Program (NTP):** None of the ingredients are listed.

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Vm&P Naphtha	The classification as a mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:** May cause drowsiness or dizziness

**Product data:**

No data available.

**Substance data:**

Name	Result
Acetone	Specific Target Organ Toxicity, Single Exposure - May cause drowsiness or dizziness.
Hydrotreated Heavy Petroleum Naphtha	Component affects the central nervous system.
Ethyl Benzene	Repeated exposure damages the hearing organs.

### Specific target organ toxicity (repeated exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Hydrotreated Heavy Petroleum Naphtha	May be fatal if swallowed and enters airway.
Ethyl Benzene	May be fatal if swallowed and enters airway.

### Information on likely routes of exposure:

No data available.

### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

### Other information:

No data available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 10 of 13

## Top Coat Silver - Aerosol

### SECTION 12: Ecological information

#### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

#### Chronic (long-term) toxicity

**Product data:** No data available.

**Substance data:** No data available.

#### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

#### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

#### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

**Other adverse effects:** No data available.


### SECTION 13: Disposal considerations

#### Disposal methods:


It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

### SECTION 14: Transport information

#### United States Transportation of dangerous goods (49 CFR DOT)

UN number	1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
UN transport hazard class(es)	2.1 
Packing group	None
Environmental hazards	None
Special precautions for user	None
Passenger air/rail	75 kg
Cargo aircraft only	150 kg

#### International Maritime Dangerous Goods (IMDG)

UN number	1950
UN proper shipping name	Aerosols, Limited Quantity
UN transport hazard class(es)	2.1 
Packing group	None
Environmental hazards	None
Special precautions for user	None

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200


Initial preparation date: 10.30.2017

Page 11 of 13

## Top Coat Silver - Aerosol

<b>EmS number</b>	F-D, S-U
<b>Stowage category</b>	For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but "Separated from" class 1 except division 1.4. For AEROSOLS with a capacity above 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2.
<b>Excepted quantities</b>	E0

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

<b>UN number</b>	1950
<b>UN proper shipping name</b>	Aerosols, flammable, Limited Quantity
<b>UN transport hazard class(es)</b>	2.1 
<b>Packing group</b>	None
<b>Environmental hazards</b>	None
<b>Special precautions for user</b>	None
<b>ERG code</b>	10L
<b>Excepted quantities</b>	E0
<b>Passenger and cargo</b>	75 kg
<b>Cargo aircraft only</b>	150 kg
<b>Limited quantity</b>	30 kg G

## SECTION 15: Regulatory information

### United States regulations

#### Inventory listing (TSCA):

74-98-6	Propane	Listed
540-88-5	T-Butyl Acetate	Listed
67-64-1	Acetone	Listed
64742-89-8	Vm&P Naphtha	Listed
64742-48-9	Hydrotreated Heavy Petroleum Naphtha	Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed

**Significant New Use Rule (TSCA Section 5):** Not determined.

**Export notification under TSCA Section 12(b):** Not determined.

**SARA Section 302 extremely hazardous substances:** Not determined.

#### SARA Section 313 toxic chemicals:

67-64-1	Acetone	Not Listed
64742-89-8	Vm&P Naphtha	Not Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed

#### CERCLA:

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 12 of 13

## Top Coat Silver - Aerosol

540-88-5	T-Butyl Acetate	Listed	5,000 lb
67-64-1	Acetone	Listed	5,000
1330-20-7	Xylene	Listed	100 lb
100-41-4	Ethyl Benzene	Listed	1,000 lb

### RCRA:

67-64-1	Acetone	Listed	U002
1330-20-7	Xylene	Listed	U239

### Section 112(r) of the Clean Air Act (CAA):

74-98-6	Propane	Listed
---------	---------	--------

### Massachusetts Right to Know:

74-98-6	Propane	Listed
540-88-5	T-Butyl Acetate	Listed
67-64-1	Acetone	Listed
64742-89-8	Vm&P Naphtha	Not Listed
64742-48-9	Hydrotreated Heavy Petroleum Naphtha	Not Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed

### New Jersey Right to Know:

74-98-6	Propane	Listed
540-88-5	T-Butyl Acetate	Not Listed
67-64-1	Acetone	Listed
64742-89-8	Vm&P Naphtha	Not Listed
64742-48-9	Hydrotreated Heavy Petroleum Naphtha	Not Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed

### New York Right to Know:

74-98-6	Propane	Listed
540-88-5	T-Butyl Acetate	Listed
67-64-1	Acetone	Listed
64742-89-8	Vm&P Naphtha	Not Listed
64742-48-9	Hydrotreated Heavy Petroleum Naphtha	Not Listed
1330-20-7	Xylene	Listed
100-41-4	Ethyl Benzene	Listed

### Pennsylvania Right to Know:

74-98-6	Propane	Listed
540-88-5	T-Butyl Acetate	Listed
67-64-1	Acetone	Listed
1330-20-7	Xylene	Listed

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.30.2017

Page 13 of 13

## Top Coat Silver - Aerosol

100-41-4

Ethyl Benzene

Listed

### California Proposition 65:

**⚠️WARNING:** This product can expose you to Ethyl Benzene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

### Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 2-4-3

**HMIS:** 2-4-3

**Initial preparation date:** 10.30.2017

**End of Safety Data Sheet**