

1 Identification

- **Product identifier**
- **Trade name:** 15011-15596 Color Coat RTS
- **Article number:**
15011, 15014, 15015, 15016, 15041, 15081, 15084, 15086, 15091, 15101, 15111, 15275, 15305, 15311, 15501, 15504, 15506, 15511, 15514, 15516, 15521, 15524, 15526, 15531, 15534, 15536, 15541, 15544, 15545, 15546, 15556, 15561, 15564, 15566, 15576, 15581, 15584, 15586, 15591, 15594, 15596, 1501-DR
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

Trade name: 15011-15596 Color Coat RTS

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

toluene

butanone

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 3)

Trade name: 15011-15596 Color Coat RTS

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

· **Dangerous components:**

108-88-3	toluene	70-100%
78-93-3	butanone	≥7- <10%
108-65-6	2-methoxy-1-methylethyl acetate	1.5-5%
2807-30-9	2-(propyloxy)ethanol	1.5-5%
100-41-4	ethylbenzene	≥0.1- ≤1%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)



Trade name: 15011-15596 Color Coat RTS

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

108-88-3	toluene	67 ppm
78-93-3	butanone	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
2807-30-9	2-(propyloxy)ethanol	2.2 ppm
1330-20-7	xylene	130 ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	18 mg/m ³
67-56-1	methanol	530 ppm
100-41-4	ethylbenzene	33 ppm
1333-86-4	Carbon black	9 mg/m ³
78-83-1	butanol	150 ppm
111-66-0	oct-1-ene	40 ppm

· **PAC-2:**

108-88-3	toluene	560 ppm
78-93-3	butanone	2700* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
2807-30-9	2-(propyloxy)ethanol	24 ppm
1330-20-7	xylene	920* ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	200 mg/m ³
67-56-1	methanol	2,100 ppm
100-41-4	ethylbenzene	1100* ppm
1333-86-4	Carbon black	99 mg/m ³
78-83-1	butanol	1,300 ppm
111-66-0	oct-1-ene	800* ppm

· **PAC-3:**

108-88-3	toluene	3700* ppm
----------	---------	-----------

(Contd. on page 5)



Trade name: 15011-15596 Color Coat RTS

(Contd. of page 4)

78-93-3	butanone	4000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
2807-30-9	2-(propyloxy)ethanol	140 ppm
1330-20-7	xylene	2500* ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	1,200 mg/m ³
67-56-1	methanol	7200* ppm
100-41-4	ethylbenzene	1800* ppm
1333-86-4	Carbon black	590 mg/m ³
78-83-1	butanol	8000* ppm
111-66-0	oct-1-ene	2000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
-----	---

(Contd. on page 6)



Trade name: 15011-15596 Color Coat RTS

(Contd. of page 5)

REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI

78-93-3 butanone

PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

· Ingredients with biological limit values:

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI	2 mg/L Medium: urine Time: end of shift Parameter: MEK
-----	---

(Contd. on page 7)

Trade name: 15011-15596 Color Coat RTS

(Contd. of page 6)

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-
 Medium: end-exhaled air
 Time: not critical
 Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid
Color: According to product specification

(Contd. on page 8)



Trade name: 15011-15596 Color Coat RTS

(Contd. of page 7)

· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	79 °C
· Flash point:	-4 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	514 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7 Vol %
· Vapor pressure at 20 °C:	29 hPa
· Density at 20 °C:	0.91393 g/cm ³
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	84.7 %
Water:	0.0 %
VOC content:	84.72 %
	774.3 g/l / 6.46 lb/gal
Solids content:	15.3 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 9)



Trade name: 15011-15596 Color Coat RTS

(Contd. of page 8)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
1333-86-4	Carbon black	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

68911-87-5 | montmorilontie clay complex

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

(Contd. on page 10)



Trade name: 15011-15596 Color Coat RTS

· **Other adverse effects** No further relevant information available.

(Contd. of page 9)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

* 14 Transport information

- | | |
|--|------------------------------------|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · DOT | Paint |
| · ADR | 1263 Paint, special provision 640D |
| · IMDG, IATA | PAINT |
| · Transport hazard class(es) | |
| · DOT | |
| | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · ADR, IMDG, IATA | |
| | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | II |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids |
| · EMS Number: | F-E, <u>S-E</u> |
| · Stowage Category | B |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

(Contd. on page 11)

USA



Trade name: 15011-15596 Color Coat RTS

(Contd. of page 10)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **ADR**

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
	Acrylic Resin
78-93-3	butanone
1330-20-7	xylene
67-56-1	methanol
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

108-88-3	toluene
78-93-3	butanone
51274-00-1	YELLOW IRON OXIDE
108-65-6	2-methoxy-1-methylethyl acetate
2807-30-9	2-(propyloxy)ethanol
1330-20-7	xylene
67-56-1	methanol
100-41-4	ethylbenzene
1333-86-4	Carbon black
68911-87-5	montmorilontie clay complex
61791-55-7	Amines, N-tallow alkyltrimethylenedi-
78-83-1	butanol
111-66-0	oct-1-ene

(Contd. on page 12)

Trade name: 15011-15596 Color Coat RTS

(Contd. of page 11)

7732-18-5	water
-----------	-------

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
1333-86-4	Carbon black

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
67-56-1	methanol

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II
78-93-3	butanone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3	toluene	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
1333-86-4	Carbon black	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

67-56-1	methanol
1333-86-4	Carbon black

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

toluene

butanone

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

(Contd. on page 13)

**Trade name: 15011-15596 Color Coat RTS**

(Contd. of page 12)

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P321 Specific treatment (see on this label).
- P314 Get medical advice/attention if you feel unwell.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Rita Joiner (rjoiner@semproducts.com)

· **Date of preparation / last revision** 10/22/2018 / 14

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 14)



Trade name: 15011-15596 Color Coat RTS

(Contd. of page 13)

HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
· *** Data compared to the previous version altered.**

USA